

RoHS Compliant

REV.	ECN NO	LTR	DESCRIPTION	REVISER	DATE
A/0			INITIAL RELEASE	ken	12.11.30
A/1			完善图面	ken	13.01.18
A/2		△	增加重点管控尺寸	ken	13.04.10
A/3		△	增加1.14±0.15mm重点管控尺寸	ken	14.04.14

NOTE:

1.MATERIAL:

INSULATOR: LCP WITH 30% G.F. COLOR:NATURE.

TERMINAL: COPPER ALLOY

TERMINAL PLATING: SELECTIVE GOLD FLASH ON CONTACT AREA.

FRONT SHELL: SPCC-SD NICKEL PLATING ON SURFACE.

TIN 100U"MIN.ON SOLDER TAIL.

2.SPECIFICATIONS CU PLATING ON BASE.

CONTACT CURRENT RATING: 0.5 AMP

CONTACT VOLTAGE RATING: 30V AC (RMS)

DIELECTRIC WITHSTANDING VOLTAGE:

250V AC FOR ONE MINUTE

INSULATION RESISTANCE: 500MEGOHMS MIN.

3.MATERIALS

CONTACTS: COPPER ALLOY,SELECTIVE GOLD PLATED

INSULATORS: THERMOPLASTIC UL94V-0 RATED.

SHELL: COLD ROLLER STEEL.

4.▽ REPRESENTS A CRITICAL DIMENSION.

5.ROHS COMPLIANT.

NO OF POS.	PART NO.	A	B	C	D	E	F	G
36	34736MW5BA1	21.80	19.15	15.40	18	19.65	15.65	17.50
50	34750MW5BC1	27.40	24.75	21.00	25	25.25	21.25	23.10
68	34768MW5AB1	34.60	31.95	28.20	34	32.45	28.45	30.30

图号(DWG NO)	G-347-S2-2	单位(UNIT):	MM	<b>深圳显赫科技有限公司</b> ShenZhen XianHe Technological co., Ltd.
型号(MODEL NO)		比例(SCALE)	1:1	
版次(REV):	A/3	页次(PAGE):	1/1	TEL:0755-27536828 FAX:0755-27536522
设计(DESIGN)	Ken	未注公差	TOLERANCE UNSPECIFIED	<b>VHDCP 夹板式 公头</b> <b>半金锡15u" LCP 本色</b>
审核(CHECKED)		X.X	± 0.15	
核准(APPROVED)		X.XX	± 0.05	
		X.XXX	± 0.03	<b>料号(PART NO)</b>
		X'.	± 0.03	
		X.X'	± 0.1	

